

CUSTOMER DISPLAYS

DM-D110



DM-D210



DM-D500



	DM-D110	DM-D210	DM-D500
Product description	<p>Clear easy-to-read display</p> <p>A high-speed data transfer display, using a high brightness panel. Also offers flash memory and extensive font table.</p>	<p>High-resolution wide angle display</p> <p>A high-speed data transfer, wide angle display, using a high brightness panel. Also offers flash memory and extensive font table.</p>	<p>Advanced high - resolution graphics display</p> <p>Designed to improve customer information at the PoS, this displays graphics and up to eight lines of text, which can be scrolled either vertically or horizontally.</p>
Display method / colour	Vacuum fluorescent / green	Vacuum fluorescent / green	Vacuum fluorescent / green
Number of characters	40 (20 columns x 2 lines)	40 (20 columns x 2 lines)	256 x 64 (42 columns x 8 lines)
Brightness	690 cd/m ²	700 cd/m ²	300 cd/m ²
Buffer size	80 bytes	80 bytes	Receive 4kb / Macro 2kb
Interface	EIA / TIA, RS232 / SERIAL	EIA / TIA, RS232 / SERIAL	EIA / TIA, RS232 / SERIAL
Baud rate	2,400 - 115.200 BPS	2,400 - 115.200 BPS	2,400 - 115.200 BPS
Connection	pass through / direct	pass through / direct	pass through / direct
Euro symbol	Supported	Supported	Supported
Character size / pitch	3.5 x 5mm / 5.2mm	6.5 x 11.3mm / 9.9mm	animated graphics
Character font	5x7 dot matrix cursor	5x7 dot matrix cursor, dec point	5x7, 8x16, 16x16 dot matrix
Character type	Alphanumeric 95 International 37 Graphics 128 x 12	Alphanumeric 95 International 37 Graphics 128 x 12	Alphanumeric 95 International 37 Graphics 128 x 12
Download characters	95	95	132 / 94
EMC standards	VCCI / FCC Class A, CE	VCCI / FCC Class A, CE	VCCI / FCC Class A, CE
Safety standards	UL / USA / TUV (EN60950)	UL / USA / TUV (EN60950)	UL / USA / TUV (EN60950)
Reliability	20,000 hrs	20,000 hrs	30,000 hrs
Power consumption	11.4 - 48VDC / 6W	11.4 - 48VDC / 6W	11.4 - 48VDC / 6W
Dimensions mm W x D x H	165 x 50.5 x 69	260 x 50.5 x 83	213 x 51 x 83
Power supply	PS180	PS180	PS180
Weight kg (approx.)			
Colour: Epson Cool-White, Dark-Grey	ECW / EDG	ECW	ECW / EDG
Mounting options	DM-D110 / 101 DM-D110 / -BA DM-D110-BB DM-D110-BC / -BD	DM-D210 / -BA DM-D210-BB DM-D210-BC / -BD	DM-D500 / 101 DM-D500 / -BA / BADG DM-D500-BB DM-D50-BC / -BD